SOLAR'S MOST TRUSTED

REC
UTICA

REC ALPHA PURE-RX SERIES

PRODUCT SPECIFICATIONS



COMPACT PANEL SIZE

9 A MODULE CURRENT
COMPATIBLE WITH MLPE

450 WP
216 W/M²

PRODUCT
REC
25 YEAR
PROTRUST
WARRANTY
PERFORMANCE
LABOR

ELIGIBLE

LEAD-FREE
ROHS COMPLIANT

EXPERIENCE
α
PERFORMANCE

REC ALPHA PURE-RX SERIES

PRODUCT SPECIFICATIONS

REC
SOLAR'S MOST TRUSTED

GENERAL DATA

Cell type:	88 half-cut REC heterojunction cells with lead-free, gapless technology
Glass:	3.2 mm solar glass with anti-reflective surface treatment in accordance with EN 12150
Backsheet:	Highly resistant polymer
Frame:	Anodized aluminum (black)
Junction box:	4-part, 4 bypass diodes, lead-free IP68 rated, in accordance with IEC 62790
Connectors:	Stäubli MC4 PV-KBT4/KST4 (4 mm²) in accordance with IEC 62852, IP68 only when connected
Cable:	4 mm² solar cable, 1.7 + 1.7 m in accordance with EN 50618
Dimensions:	1728 x 1205 x 30 mm (2.08 m²)
Weight:	23.2 kg
Origin:	Made in Singapore



Measurements in mm

ELECTRICAL DATA

	Product Code*: RECxxxAA Pure-RX
STC	
Power Output - P_{MAX} (Wp)	450
Watt Class Sorting - (W)	0/+10
Nominal Power Voltage - V_{MPP} (V)	54.3
Nominal Power Current - I_{MPP} (A)	8.29
Open Circuit Voltage - V_{OC} (V)	65.1
Short Circuit Current - I_{SC} (A)	8.81
Power Density (W/m²)	216
Panel Efficiency (%)	21.6
NMOT	
Power Output - P_{MAX} (Wp)	343
Nominal Power Voltage - V_{MPP} (V)	51.2
Nominal Power Current - I_{MPP} (A)	6.70
Open Circuit Voltage - V_{OC} (V)	61.3
Short Circuit Current - I_{SC} (A)	7.11

Values at standard test conditions (STC: air mass AM 1.5, irradiance 1000 W/m², temperature 25°C), based on a production spread with a tolerance of P_{MAX}, V_{OC} & I_{SC} ±3% within one watt class. Nominal module operating temperature (NMOT: air mass AM 1.5, irradiance 800 W/m², temperature 20°C, windspeed 1 m/s). * Where xxx indicates the nominal power class (P_{MAX}) at STC above.

CERTIFICATIONS

IEC 61215:2016, IEC 61730:2016, UL 61730	
IEC 62804	PID
IEC 61701	Salt Mist
IEC 62716	Ammonia Resistance
ISO 11925-2	Ignitability (EN 13501-1 Class E)
IEC 62782	Dynamic Mechanical Load
IEC 61215-2:2016	Hailstone (35mm)
IEC 62321	Lead-free acc. to RoHS EU 863/2015
IEC 61730-2:2016	Fire Class C (as per UL 790)
ISO 14001, ISO 9001, IEC 45001, IEC 62941	

Lead-Free

take-e-way WEEE-compliant recycling scheme

TEMPERATURE RATINGS*

Nominal Module Operating Temperature:	44°C (±2°C)
Temperature coefficient of P_{MAX}:	-0.24 %/°C
Temperature coefficient of V_{OC}:	-0.24 %/°C
Temperature coefficient of I_{SC}:	0.04 %/°C

*The temperature coefficients stated are linear values

MAXIMUM RATINGS

Operational temperature:	-40 ... +85°C
Maximum system voltage:	1000 V
Maximum test load (front):	+7000 Pa (713 kg/m²)*
Maximum test load (rear):	-4000 Pa (407 kg/m²)*
Max series fuse rating:	25 A
Max reverse current:	25 A

* See installation manual for mounting instructions. Design load = Test load / 1.5 (safety factor)

WARRANTY

	Standard	REC ProTrust	
Installed by an REC Certified Solar Professional	No	Yes	Yes
System Size	All	≤25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%

The REC ProTrust Warranty is only available on panels purchased through an REC Certified Solar Professional installer. Warranty conditions apply. See www.recgroup.com for more details.

DELIVERY INFORMATION

Panels per pallet:	33
Panels per 40 ft GP/high cube container:	594 (18 pallets)

LOW LIGHT BEHAVIOUR

Typical low irradiance performance of module at STC:



Specifications subject to change without notice.

Ref: PM-DS-12-06-Rev- 2.2 05.23

UTICA™
www.utica.sg